



Nieuwstraat 51 - 5521 CB Eersel, The Netherlands  
 Tel.: +31-6-46270636  
 Email: info@seuic-emea.com

**Fashionable appearance**

Fashionable appearance, contracted style



**Easy to operate**

Simple, easy to operate panel design



**Easy paper loading**

Quick and easy drop paper design



**Specification:**

**MODEL SE-P800**

Printing method	Direct thermal
Printing speed	50mm/s
Paper width	79.5±0.5mm
Roll paper	40mm
Paper thickness	0.06-0.08mm
Column capacity	576 dots/line
Character size	ANK, Font A: 12x24 dots Font B: 9x17 dots simplified/traditional Chinese: 24x24 dots
Line space	3.75mm (changeable using commands)
Interface	Bluetooth+USB+Serial
Barcode	1D Barcode: UPC-A /UPC-E/JAN13 (EAN13) / JAN8 (EAN8) / CODABARITF/CODE39/CODE93/CODE 128 2D Barcode: QR CODE/PDF417
Extended characters	PC347 (Standard Europe I , Katakana, PC850 ( Multilingual I , PC860 ( Portuguese I , PC863 ( Canadian-French I , PC865 ( Nordic I , West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 ( Cyrillic#2 I , PC852 ( Latin2 I , PC858, IranII, Latvian, Arabic, PT151 ( 1251)
Auto cutter	--
NV FLASH	64 K Bytes
Input buffer	32 K Bytes
Power supply	Input: AC 110V/240V, 50/60Hz
Power	Output: AC 9.5V/2A
Battery	2000mAh
Reliability	Printing head life: 50 km
Working environment	Temperature (0-45°C, humidity (10-80%)
Storage environment	Temperature (-10-60°C), humidity (10-90%)
Operating system	Win 9X/Win 2000/Win 2003/Win XP/Win 7/Win 8/Win 8.1/Linux/IOS/Android
Print command	Compatible with ESC/POS
Gross weight	0.21 kg
Dimension	108.5 x 105 x 48mm (L x W x H)