



Nieuwstraat 51 - 5521 CB Eersel, The Netherlands
 Tel.: +31-6-46270636
 Email: info@seuic-emea.com

SPECIFICATIONS

SPECIFICATIONS		Picture
Model No.	SE-P100	
Printing method	Direct Thermal	
Resolution	384dots/line	
Character size	ANK, Font A: 12x24dots; Font B: 9x17dots Simplified Chinese, traditional Chinese: 24x24dots	
Character set	user option	
Printing speed	70mm/sec	
Input buffer	32k bytes	
NV flash buffer	64k bytes	
Paper width	57.5±0.5mm	
MCBF(life)	50km	
Dimensions	92.5x75.5x37mm	
Net weight	0.19kg	
Auto cutter	without	
Roll paper	57.5±0.5mm* φ30mm	
battery life	2300mAh, 2 hours working continuously, 7 days standby time	
Power supply	Input: AC 110V/220V,50~60Hz	
Power adapter	Output: DC 9.5V/1A	
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/win 7 Win 8/ Win 8.1	
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODE39/ITF/CODABAR/CODE93/CODE128	
Storage environment	temperature (-10~60°c) humidity(10~90%)	
Working environment	temperature (0~45°c) humidity(10~80%)	
Command	Compatible with EPSON ESC/POS	
Interface	Serial/USB/bluetooth	



Nieuwstraat 51 - 5521 CB Eersel, The Netherlands
 Tel.: +31-6-46270636
 Email: info@seuic-emea.com